



HIGHWAY

HT60-156M HT60-156M(V) * V means 1500V module Black Module Technology 300W-320W

Comprehensive and first-rate certification system

UL 1703 Latest Standard

IEC61215:2016, IEC61730:2016 Latest Standard

ISO9001, ISO14001 and OHSAS18001, meeting the

highest international standards

Strict quality control



IEC 61215:2016
IEC 61730:2016



Advanced surface treatment, less surface reflection and 5BB cell design can reduce the series resistance and improve the module



19.7%
Module Efficiency



Designed for high voltage systems of up to 1500VDC, increasing the string length of solar systems and saving on BoS costs



Certified to withstand dynamic mechanical load 1000 Pascal




Higher module's output power



PID resistant



Ammonia corrosion resistant
Salt Mist corrosion resistant




Microcrack resistant
Triple EL tested of high quality control



Entire module certified to withstand extreme wind (2400 Pa) and snow loads (5400 Pa)





Strict quality control, meeting the highest international standards: ISO 9001, ISO14001



All the modules are sorted and packaged by amperage, reducing mismatch losses and maximizing system output.

Engineering Drawing



Electrical Characteristics

Module	HT60-156M / HT60-156M(V)				
	300W	305W	310W	315W	320W
Maximum Power at STC(Pmax)	300W	305W	310W	315W	320W
Open-Circuit Voltage(Voc)	39.9V	40.1V	40.3V	40.5V	40.7V
Short-Circuit Current(Isc)	9.71A	9.78A	9.85A	9.92A	9.99A
Optimum Operating Voltage (Vmp)	32.8V	33.2V	33.6V	34.0V	34.4V
Optimum Operating Current(Imp)	9.16A	9.21A	9.25A	9.29A	9.33A
Module Efficiency	18.4%	18.8%	19.1%	19.4%	19.7%
Power Tolerance	0 ~ +5W				
Maximum System Voltage	1000V/1500V DC (UL/IEC)				
Maximum Series Fuse Rating	15A/20A				
Operating Temperature	-40 °C to +85 °C				

STC: Irradiance 1000W/m², module temperature 25°C, AM=1.5
Optional black frame or white frame module according to customer requirements

NOCT

Module	HT60-156M / HT60-156M(V)				
	221W	225W	229W	232W	236W
Maximum Power	221W	225W	229W	232W	236W
Open Circuit Voltage (Voc)	37.2V	37.4V	37.6V	37.8V	38.0V
Short Circuit Current (Isc)	7.84A	7.90A	7.96A	8.01A	8.07A
Maximum Power Voltage (Vmp)	30.5V	30.9V	31.3V	31.7V	32.1V
Maximum Circuit Current (Imp)	7.24A	7.27A	7.31A	7.33A	7.36A

NOCT: Irradiance 800W/m², ambient temperature 20°C, wind speed 1 m/s

Mechanical Characteristics


Solar Cells	Monocrystalline 156.75 × 156.75mm
No. of Cells	60 (6 × 10)
Dimensions	1640 × 992 × 35mm (64.6 × 39.1 × 1.4in)
Weight	18.5kg (40.8lbs)
Front Glass	High transmission tempered glass
Frame	Anodized aluminium alloy
Junction Box	IP67
Cable	4mm² (UL/IEC)
Connectors	MC4/MC4 Compatible
Packaging Configuration	30pcs/box, 910pcs/40'HQ Container

Temperature Characteristics

Temperature Coefficient of Pmax	$\gamma (P_m)$	-0.365%/°C
Temperature Coefficient of Voc	$\beta (V_{oc})$	-0.275%/°C
Temperature Coefficient of Isc	$\alpha (I_{sc})$	+0.063%/°C

Warranty

- 12ys 12-year product warranty
- 25ys 25-year warranty on power output



Information Box

Shanghai Aerospace Automobile Electromechanical Co., Ltd.
Website: <http://htsolar.com.tr/>
Email: trinfo@ht-sae.com
Factory: HT SOLAR ENERJI ANONIM SIRKETI
Lianyungang ShenZhou New Energy Co., Ltd.